

HYB.12.US 80V-145A MAX 11,4KW LITIO TN						
80V – 145A						
FIRMWARE VERSION	B0052P10					
24V Battery Setting	0A/100Ah	W	C=0Ah	I=0A	U S E R M O D E M A N U F A C T U R E R M O D E	
36V Battery Setting	0A/100Ah	W	C=0Ah	I=0A		
48V Battery Setting	0A/100Ah	W	C=0Ah	I=0A		
72V Battery Setting	0A/100Ah	W	C=0Ah	I=0A		
80V Battery Setting	20A/100Ah	W	C=600Ah	I=120A		
V.GAS-GAS LIMIT	2.07 V/cel					
V.MAX-MAX LIMIT	2,14 V/Cel					
MAX TEMPERATURE	DISABLED					
FOLDBACK CURRENT	DISABLED					
EQUALIZE MODE	1 H					
DD/MM/YY hh:mm	-6H					
DAYLIGHT SAVING	GMT +6h CN.AMERIC					
ON.CH START>STOP	00:00 23:59					
OVERC START>STOP	00:00 23:59					
EQUAL. START ON	FRI 00:00					
EQUAL. START OFF	FRI 01:00					
BATTERY MODULE	VOLTAGE RECOGN.					
AMP% EQ CURRENT	2 %Cn					
SET: VOLT	—					
SET: AMPS	—					
MANUAL SERV. MODE	REL1 OFF					
DROP CABLE VOLT	12.COEF					
T-MAX TIME FULLCH	1 m					
MAX POWER	11400 Watts					
MAX TEMP DC PLUG	DISABLED					
SPEC.P1 - SPEC.P2	0 - 0					
CHARGER IDENTITY	69007					
INERNAL PARAM	DISABLED					
DISPLAY CURRENT	150A					
NOMINAL CURRENT	200 A					
MAX VOLT BATTERY	80VDC					